

TRAILED MISTBLOWER

# OASIS



## TECHNICAL CHARACTERISTICS

Capacities: 600, 800, 1.000, 1.500, 2.000 and 3.000 liters.

Electric remote control 2 ways (on/off)

Straight drawbar with tow eye

Adjustable jockey wheel

Parking brake (chocks)

Lights and reflectors

Powder mixer

Double adjustable nozzle holders with anti-drop system

Adjustable "V" deflector

Reinforced PTO shaft G7 1200mm

5 meter Ø50 floating loader

600L wheels: 185/65 R14"; 1000L wheels: 10.0/80-12"; 1000L wheels: 10.0/80-12

Wheels 1500/2000L: 10.0/75-15,3"; 1500/2000L wheels: 10.0/75-15,3

Wheels 3000L: 11.5/80-15.3".

The chassis of the 3000L model is reinforced

### Features of the Oasis blueberry model

Wheel 600 L: 185/65 R14; 800/1000 L: 70.50 R16

Overall width 600 L: 1020 mm; 800/1000 L: 1080 mm

V-shape swivel drawbar

Homokinetic PTO shaft

	Oasis				
	600 L	1000 L	1500 L	2000 L	3000 L
<b>Length (mm)</b>	3000	3820	4050	4280	4570
<b>Width (mm)</b>	1020	1310	1380	1500	2270
<b>Height (mm)</b>	1300	1530	1570	1600	1670
<b>Weight (kg)</b>	350	390	640	640	990



Model	Performance				VEL.
	Ángulo ataque	(R.P.M.)	(m³/h)		
700 MSA OASIS	30º	540	40.700	2	
	35º	540	48.500		
<b>Predistri.</b>	<b>Clutch</b>	<b>Nº blades</b>	<b>Nº Gets</b>		
No	No	8 Nylon	14		

Model	Performance				VEL.
	Ángulo ataque	(R.P.M.)	(m³/h)		
820 MSB OASIS	30º	540	54.000	2	
	35º	540	56.000		
<b>Predistri.</b>	<b>Clutch</b>	<b>Nº Palas</b>	<b>Nº Gets</b>		
Si	No	8 Nylon	14		

Model	Performance				VEL.
	Ángulo ataque	(R.P.M.)	(m³/h)		
920 M60 OASIS	30º	540	70.000	2	
	35º	540	80.000		
<b>Predistri.</b>	<b>Clutch</b>	<b>Nº blades</b>	<b>Nº Gets</b>		
Si	No	9 Nylon + Fibra	14		