

TRAILED PNEUMATIC SPRAYER

EUROVID



TECHNICAL CHARACTERISTICS

Capacity: 1,500 and 2,000 liters
2-way electrical control (on/off)
Self-cleaning outlet filters, suction filter
Lights and catadioptric
Interior cleaning robot
Centrifugal unit 8 outlets
Double turbine 500mm in balanced steel
Cast steel multiplier (M47 1:7,5)
1 speed + P.M.
Ferodo clutch 60hp
16 Double fixed nozzle holders with anti-drip system
Nozzles ALBUZ ATR-MGA red
Nozzles ALBUZ ATR-MGA yellow
Treatment of 2 complete rows
Air volume 16.000m ³ /h
High air outlet speed (100 m/s)
4+4 adjustable outlet nozzles (2 jets per hand)
Pneumatic suspension
Hydraulic lift (own hydraulic connection)
Joystick 4 buttons 5-F (opening/G.V./raising)
Hydraulic opening/closing of arms
Manual positioning
Variable geometry (V.G.)
Straight drawbar with tow eye
Adjustable jockey wheel
Parking brake (chocks)

	EuroVid 4.0	
	1500 L	2000 L
Length (mm)	4000	4100
Width (mm)	2280	2280
Height (mm)	2510	2550
Weight (kg)	850	880

