

LINKAGE SPRAYER

MIXTO



LOW PRESSURE TECHNICAL CHARACTERISTICS

Low crops (low pressure)
Capacities: 400, 600, 800, 800, 1,000, 1,200 and 1,500 liters
Exclusive FG Group design tank
Non-volumetric 3-way manual control
External level with floating ball
Self-cleaning outlet filter
Suction filter with valve
Chassis made of folded sheet metal and tubular profiles
Folding side step (600-800-1000-1200-1500L)
Reinforced PTO shaft
5-meters charger

HIGH PRESSURE TECHNICAL CHARACTERISTICS

Trees and gun treatments (medium pressure)
Exclusive FG Group design tank
Brass manual control with taps and pressure gauge
External level with floating ball
Self-cleaning outlet filter
Suction filter with valve
Chassis made of folded sheet metal and tubular profiles
Folding side step (600-800-1000-1200-1500L)
Reinforced PTO shaft
5-meters charger

	Mixto							
	200 L	300 L	400 L	600 L	800 L	1000 L	1200 L	1500 L
Length (mm)	700	700	1060	1060	1080	1080	1080	1150
Width (mm)	850	950	1430	1430	1780	1780	1780	1900
Height (mm)	1150	1220	1340	1630	1630	1790	1950	2000
Weight(kg)	80	100	150	175	200	250	270	300

